



RECOMMENDED PCB LAYOUT
TOLERANCE 0.05
STENCIL THICKNESS 0.10mm

- NOTES:
1.MATERIAL:
HOUSING:LCP
CONTACT:C7025-TM03 T=0.20MM
SHELL:SUS304-3/4H T=0.30MM
2.PRODUCT SPECIFICATIONS:
3-1 Voltage: 12V AC
3-2 Current: 3A
3-3 OPERATION TEMPERATURE:-45TO*+85
3-4 STORAGE TEMPERATURE:-45TO*+85
3.ALL DIMENSIONS MARKED ▼ MUST BE CONTROLLED BY QC.
ALL DIMENSIONS MARKER (X) MUST BE MEASURE BY FAI
4.GP PASSED ACCORD WITH HRD-RDHS-219 STANDARD.

CONTACT NO.	SIGNAL NO.
1	VBUS
2	D-
3	D+
4	ID
5	GND
SHELL	SHIELD

DESCRIPTION	MATERIAL	FINISH	Q'TY
SHELL	SUS304-3/4H	80-120u" NI MIN UNDERPLATED OVERALL 50-100u"MATTE TIN PLATED ON SOLDER AREA	1
CONTACT	C7025-TM03	30u"MIN.GOLD PLATED ON CONTACT AREA, 1u"-3u"MIN.GOLD PLATED ON SOLDER TAILS, 50u"MIN.NICKEL UNDERPLATING OVERALL	5
HOUSING	LCP	LCP ,BLACK,JUL 94V-0	1

REV.	ECN NO.	DESCRIPTION	DATE	REV.	FINISH	SEE NOTE	DRAW:	PART NO:
A		NEW	04/02/2018	A	SEE NOTE			U50-AB05D250
							CHECKED:	TITLE: MICRO USB SPIN
							APPROVE:	Drawing No: 磁上锁口成内磁卡片

