



- NOTES:
- MATERIAL:  
BODY:LCP, BLACK, UL 94V-0  
TERMINAL:COPPER ALLOY C5240, T=0.10mm  
SHELL:STAINLESS STEEL
  - FINISH:  
TERMINA:50U" NI UNDERPLATED OVER ALL  
15U" AU ON CONTACT AREA  
TIN 60-200U" PLATING ON SOLDER TAIL AREA  
SHELL:50U" NI MIN UNDERPLATED OVER ALL  
1U" AU PLATING ON SOLDER TAIL AREA
  - Rated Current: 2A/PIN MIN
  - ALL DIMENSIONS MARKED ▼ MUST BE CONTROLLED BY QC
  - ALL DIMENSIONS MARKER (XX) MUST BE MEASURED BY FAI.
  - GP PASSED ACCORD WITH HRD-ROHS-219 STANDARD

				UNITS: mm	GENERAL TOLERANCE	DRAW:	PART NO: B55-AB03C15A
C	E1908499A	调整尺寸管控	08/30/2019	DATE: 12/22/2017	X. ±0.25 X' ±0.20	CHECKED:	NAME: 1.5H side pressure Battery
B	E1810492A	成品端子头 折弯管控更新	11/03/2018	SCALE: 10:1	.XX ±0.10 .XXX ±0.05	APPROVE:	DRAWING NO: A-B55-0000_C
A		NEW	12/22/2017	SHEET: 1/1	TITLE: ASSEMBLY DRAWING		
REV.	ECN NO.	DESCRIPTION	DATE	REV. A	FINISH: SEE NOTE		

